



MVC-200 3G Camera

Get the live view without borders

Teltonika MVC-200 3G Camera - compact mobile surveillance and monitoring system for transmission of high resolution video and single images via 3G mobile network even in places with no Internet connection available. It is ideal for remote surveillance and monitoring of temporary or distant sites or mobile assets. Teltonika camera saves installation time and cost as no wired cable installation is required on the clients' premises. The video can be acquired automatically by schedule, on motion detection and/or upon external triggers such as motion sensors or door contacts. The video and single images can be viewed on a PC, and can also be transmitted by e-mail. The video and single images can be recorded on a local SD card and later downloaded or reviewed via built-in Web server.

Main features:

- Video and/or single snapshot images
- H.264 and JPEG compression
- Images can be saved on a local SD card
- Lens can be selected according to user requirements and needs
- Two-way audio transmission (talk back feature)
- Built-in Web server for monitoring via standard browser
- UMTS single, dual or tri band (850/900/1900/2100 MHz available)
- GSM quad band (850/900/1800/1900 MHz)
- Video transmission speed up to 5.76 Mbps (HSUPA).





Camera functions

- Image Sensor: 1/3" Sony CCD matrix
- Lens: C/CS mount

Supported resolution

- D1 (720x576)
- Half D1 (720x288)
- CIF (352x288)
- QCIF (176x144)

Framerate

- up to 25 fps in all resolutions

Supported image/video compression format

- H.264
- JPEG

Images stored/recorded in

- SD card inserted in camera (max card size 32 GB)
- PC (HDD)

Image/video transmitting/recording

- By scheduler
- On motion detection
- Alarm input (e.g. PIR sensor, door contact, etc)

Motion detection

- 4 areas with different sensitivity
- Recording to SD card, e-mail and/or relay contacts triggering

OSD (On Screen Display)

- Camera name
- Date/Time
- User defined text

Videomasking

- Allows to mask out privacy zone

Video review

- Via camera's WEB-interface
- E-mail (single images, video clips)
- Video streaming

Audio

- Two-way audio transmission
- Talk-back function

Time synchronization

- Manual
- Via PC
- NTP Time-Server

Management

- Firmware update

Power

- 12V DC, Average 0.38A, MAX 0.5A

Other

- Software to watch multiple cameras at once
- Control of external equipment (relay contacts)
- Dimensions (without lens) 140x65x65 mm.
- Temperature -10 °C to +55 °C
- Humidity 10% to 90%

Please note: The product specifications may change without prior notice.

HQ JSC Teltonika

Saltoniskiu st. 10c
LT-08105, Vilnius
Lithuania

Tel +370 5 212 74 72 (Lithuania)
Tel +370 5 265 73 60 (International Calls Landline)
Tel +370 5 265 73 61 (Landline)
Fax +370 5 276 13 80
Email info@teltonika.lt
Web www.teltonika.lt

Teltonika International GmbH

Rosenstraße 2
10178 Berlin
Germany

Tel +49 30 243102 205
+49 30 243102 206
Fax +49 30 243102 22
Email info.de@teltonika.com
Web www.teltonika.de

Teltonika International Oy

Kutomotie 18 B
00380 Helsinki
Finland

Tel +358-9-565 96220
Fax +358-9-565 96300
Email info.fi@teltonika.com
Web www.teltonika.com